

## 850S Paper

Paper mail order fulfilment packaging machine

A sustainable and high-speed solution for mail order fulfillment and e-commerce applications





## 850S Paper

Paper mail order fulfilment packaging machine

A sustainable and high-speed solution for mail order fulfillment and e-commerce applications



### FEATURES AND BENEFITS

- Runs all-paper bags that are 100% curbside recyclable.
- High-quality seals and optional resealable capabilities for returns.
- Currently capable of running 480mm\* wide paper bags.
- High-quality seals and optional resealable capabilities for returns.
- Opens, labels, and seals 7 to 10 bags per minute.
- Capable of printing high resolution shipping labels directly on the bags.
- Features an intuitive interface for easy access to help systems, diagnostics, and performance monitoring, simplifying maintenance and maximizing productivity.
- Reduces shipping costs compared to corrugated boxes.
- Simple bag threading for fast and easy changeover.
- Can be networked for full pack station integration to facilitate central monitoring and the extraction of productivity information.

### TYPICAL APPLICATIONS



E-Commerce Returns Processing



Fulfilment Centre



Accessories



Apparel

### SUSTAINABILITY



100%  
KERBSIDE RECYCLABLE

As a maker of flexible packaging products, we recognise the need for greater awareness and involvement in creating a more sustainable planet – from the point of manufacture to the point of disposal.

For over a decade, we have been producing environmentally responsible products for our customers. We introduced GeoTech®, a line of pre-consumer reprocessed films that forever changed the packaging industry. We have introduced innovative, lighter gauge films that reduce the amount of material required without compromising packaging performance. In addition, our machinery technology continues to evolve with new, state-of-the-art components and engineering designed to reduce energy consumption.

#### SPECIFICATIONS

Weight	318 kg
Overall Size	H: 1105 to 1410 mm W: 1150 mm L: 1829 mm
Electrical	110/240 VAC, 50/60 Hz, 1000 Watts (VA) max
Air Feed	5 CFM/80 psi of clean, dry air
Pass-through**	150 mm max
Bag widths*	355-480 mm
Bag lengths*	480-600 mm

\*Fillable sizes

\*\*Information subject to change

